



Shrink Wrapping Machines



Semi-Auto Sleeve Sealing & Shrink Packaging

Technical Specifications:



Model	JPI-6030S	ST6040
Machine Dimension LxWxH (mm)	1129x1305x1991	2400x900x1690
Tunnel Dimension LxWxH (mm)	~	1500x600x400
Max. Packing Size LxWxH (mm)	500x300x300	1300x400x300
Sealing Size L (mm)	700	~
Temperature (°C)	0-200	0-400
Height of Worktable	850 ±50	850 ±50
Packing Speed (pcs/min)	5-8	20-25
Net Weight (kg)	300	500/550
Power (kW)	1	2
Power Supply	3PH, 220V/380V, 50/60 Hz	
Air Pressure (kg/cm ²)	6-8	~
Applicable Film	PE	PE

Auto Sleeve Sealing & Shrinking Machine

Technical Specifications:



Model	JPI-6030AH	ST6040
Machine Dimension LxWxH (mm)	1348x2716x1991	2800x900x1690
Tunnel Dimension LxWxH (mm)	~	1800x600x400
Max. Packing Size LxWxH (mm)	400x300x300	1500x400x300
Sealing Size L (mm)	700	~
Temperature (°C)	0-200	0-400
Height of Worktable	850 ±50	850 ±50
Packing Speed (pcs/min)	6-14	25-30
Net Weight (kg)	490	650
Power (kW)	1.5	24
Power Supply	3PH, 220V/380V, 50/60 Hz	
Air Pressure (kg/cm ²)	6-8	~
Applicable Film	PE	PE

Front Feeding, Auto Sleeve Sealing & Shrinking Machine

Technical Specifications:



Model	JPI-6030Z	ST6040
Machine Dimension LxWxH (mm)	1382x2716x1991	2800x900x1690
Tunnel Dimension LxWxH (mm)	~	1800x600x400
Max. Packing Size LxWxH (mm)	400x300x300	1500x400x300
Sealing Size L (mm)	700	~
Temperature (°C)	0-200	0-400
Height of Worktable	850 ±50	850 ±50
Packing Speed (pcs/min)	8-15	25-30
Net Weight (kg)	600	600
Power (kW)	1.2	24
Power Supply	3PH, 220V/380V, 50/60 Hz	
Air Pressure (kg/cm ²)	6-8	~
Applicable Film	PE	PE

L - Type Sealer



Semi-Auto L-Type Sealer

JPI-SS1011



Electro Magnetic L-Type Sealer

JPI-SS1012



L-Type Hood Shrink Packaging Machine

JPI-SS1013



Heavy Duty Semi-Auto L-Type Sealer

- ✓ Used for shrink packaging of variety of products
- ✓ Can be used with PE, POF, PVC types films
- ✓ Smoke & Fume less sealing process
- ✓ Timer controlled sealing process for accurate operation
- ✓ Ideal for shrink packaging
- ✓ Availability of inbuilt Air compressor
- ✓ Low power consumption
- ✓ Faster and accurate operation
- ✓ Can be shifted conveniently from one place to another with the help via casters
- ✓ Ideal for limited space supermarkets, laboratories or offices

JPI-SS1014

Shrink Packaging Machines - Tunnel Type



Shrink Packaging Machine

JPI-SS1021



PE Shrink Packaging Machine

JPI-SS1022



Shrink Packaging Machine

JPI-SS1023



Shrink Packaging Machine (High Speed Model)

JPI-SS1024

- ✓ Can be used to shrink pack a wide variety of products
- ✓ Can be used with PP, OPP, PE, POF, PVC type films
- ✓ Auto temperature control to reduce electricity consumption
- ✓ Smoke & Fume less sealing process
- ✓ Can accommodate large products easily for shrink packaging
- ✓ Coveyor speed of 0-10 metre/minute
- ✓ Option to use both Roll type & Net type conveyer belt for different products
- ✓ Option to select from heat conduction type & heat circulation type model
- ✓ Conveyer speed control by precision electric stepless type motor



Shrink Tunnel

JPI-SS1025

Automatic Sealing and Shrink Wrapping Machine



- ✔ Equipped with PLC control system and safety protecting and alarm devices
- ✔ Constant sealing with no need of changing.
- ✔ Easy to operate and maintain
- ✔ Automatically adjustable shrink film length
- ✔ The added horizontal and vertical electric eyes provide options for switchover. It's suitable for sealing thin and small products.
- ✔ Automatically perform the scraps discharge process. Leave no mess & keep your work space tidy & clean.
- ✔ The machine can be used in food, gift hardware, pharmacy and printing industries.

Technical Specifications:

	JPI-SS1033-S1	JPI-SS1033-S2
Tunnel Size (L x W x H) (in mm)	1000 x 450 x 250	550 x 450 x 250
Conveyor Speed	0 - 12 (M/min)	15 - 25 pcs
Load Capacity (kg)	10	~
Heater Power (Kw)	10kw	2 kw
Dimensions (L x W x H) (in mm)	1300 x 715 x 1455	1790 x 850 x 1525
Input Voltage (V/Hz)	220V / 380 V, 50 / 60 Hz, 3 phase	220V / 380 V, 50 / 60 Hz, 3 phase
Air Compressing (kg / cu. cm)	5.5	5.5

High Speed Side Sealing and Shrinking Machine

- ✔ Can be combined with automatic production line
- ✔ Adjustable front feed system
- ✔ Hi-speed hot air circulating shrink tunnel
- ✔ Adjustable tunnel temperature for PE, PVC & POF films



Technical Specifications:

	JPI-5545H	JPI-5030LW
Power Supply	220 V, 1 Ph, 50-60 Hz	380 V, 3Ph, 50-60 Hz
Power	3 kW	16 kW
Packing Size (L x W x H) (mm)	∞ x 450 x 150	1200 x 450 x 250
Tunnel Size (L x W x H) (in mm)	W 520	1500 x 500 x 300
Packing Speed (pcs/min)	20 - 60	20 - 60
Air Compressing (kg / cu. cm)	5.5	~
Max Current	10 A	32 A
Dimensions (L x W x H) (in mm)	2050 x 1580 x 1740	2000 x 1100 x 1250
Net Weight (kg)	800	650

Automatic L-Bar Sealing and Shrinking Machine

- ✔ Heat resistant and anti-adhering material coating from Du Pont on cutter
- ✔ Horizontal and Vertical sensor for thin and small products
- ✔ Automatic product feeder, waste film collecting system
- ✔ Packing product protection system
- ✔ Safety cover device with alarm system



Technical Specifications:

	JPI4535	JPI4525
Power Supply	220V, 1Ph, 50-60 Hz	380V, 3Ph, 50-60 Hz
Power	2 kW	10 kW
Packing Size (L x W x H) (mm)	500 x 430 x 100	500 x 400 x 200
Tunnel Size (L x H x H) (mm)	550 x 450	1000 x 450 x 250
Packing Speed (pcs/min)	1 - 25	20 - 40
Air Compressing (kg / cu. cm)	5.5	5.5
Max Current	10A	30A
Net Weight (kg)	250	185
Machine Dimensions (L x W x H) (mm)	1830 x 850 x 1550	1300 x 715 x 1455

Automatic High Speed Side Sealing and Shrinking Machine

- ✔ Stable machine operation at higher speeds
- ✔ Straight & tight sealing using vertical cutting system
- ✔ Unlimited product length support
- ✔ Adjustable sealing height
- ✔ Suitable for wide sizes and shapes of products



Technical Specifications:

	JPI-5545C	JPI-5030S
Power Supply	220V, 1 Ph, 50-60 HZ	380V, 3 Ph, 50-60 HZ
Power	3 kW	16kW
Packaging Size (L x W x H) mm	∞ x 450 x 150	1200 x 450 x 250
Tunnel Size (L x W x H) (in mm)	length : 520 mm	1500 x 500 x 300
Packing Speed (pcs/min)	20 - 60	20 - 60
Air Compressing (kg / cu. cm)	5.5	~
Max Current	10A	32A
Net Weight (kg)	800	650
Dimensions (L x W x H) (in mm)	2050 x 1580 x 1740	L20

Shrink Tunnel



- ✔ Hot-wind & down-cyclone structure with intelligent temperature control feature
- ✔ AC speed regulation feature
- ✔ Option of Teflon mesh belt, Roller type or Net type conveyor belt
- ✔ Adjustable tunnel and shutter height for ease of use
- ✔ Option of single / double hot wind tunnel for different products
- ✔ Can be used with PVC, POF, PP etc. films
- ✔ Adjustable conveyor speed by precision electric step-less instrument
- ✔ Infrared ray heater for maximum compatibility with different sized product & shrink wrap films

Technical Specifications:

	JPI-ST1031-S1	JPI-ST1031-S2	JPI-ST1031-L1	JPI-ST1031-L2
Tunnel Size (L x W x H) (in mm)	900 x 300 x (50~200)	900 x 450 x (50~250)	1200 x 450 x (50~350)	1200 x 650 x (50~350)
Conveyor Speed (m/min)	0 - 10	0 - 10	0 - 10	0 - 10
Load Capacity	10	10	30	30
Power (Kw)	5.1	6.5	9.6	9.6
Dimensions (L x W x H) (in mm)	1200 x 500 x 1050	1200 x 650 x 1100	1600 x 650 x 1200	1600 x 850 x 1200
Input Voltage (V/Hz)	220/50 380/50 (3 PH) 220/60 (3 PH)		380/50 (3 PH) 220/60 (3 PH)	
Machine Weight (kg)	60	90	120	150

Heavy Duty Shrink Tunnel



- ✔ Solid robust fabrication with powder coated structure and SS Cladding
- ✔ Stainless Steel Roller
- ✔ Digital Temperature controller Variable Speed (AC frequency inverter drive)
- ✔ Modular fan for cooling tower
- ✔ Stainless Steel Fin type heaters
- ✔ Can be used for packaging of Food & Beverages, Dairy Products, Liquor & Fruit Juice bottles

Technical Specifications:

Chamber Opening	In-feed Conveyor	Out-feed Conveyor	Dimension (in mm)	Power
750x300mm	600mm	1250mm	1150L x 600W	440V 20kwh, 3ph.

JPI-ST1042

JOY PACK INDIA Product Spectrum

Our area of specialization is based on the varied packaging requirements of diverse industries. The comprehensive product line that we present, is a result of a combination of many things like quality raw materials, advanced machinery, competitive prices etc. In addition to our showcased range of packaging machines, we also manufacture the following:

- ✔ **Web Sealer**
- ✔ **Strapping Machines**
- ✔ **Taping / Carton Sealer**
- ✔ **Stretch Wrapping Machines**



JOY PACK INDIA PVT. LTD.
46, Suvidha Kunj, Pitam Pura
New Delhi - 110034 INDIA

Phone: +91 9810023485 / 9312235318

Fax: +91 11 4750 2936

Email: info@joypackindia.com

WWW.JOYPACKINDIA.COM