



Carton / Box Wrapping Machine



✓ Power Consumption	1 Phase, 220 V, 50 Hz, 1 kw
✓ Turntable Speed	0-20 round per minute
✓ Lifting Unite	Photoelectric switch for height control
✓ Film Stretching Unit	Frequency regulation (pre-stretch)
✓ Max. Package Weight	80 kg
✓ Pacakage Size (L x W x H)	(250~1200) x (200~400) x (250~1200) mm
✓ Machine Dimension (L x W x H)	1600 x 600 x 1740 mm
✓ Machine Weight	150 kg

JPI-SW3001

Carton Wrapping Machine



✓ Power Consumption	1 Phase, 220 V, 50 Hz, 1 kw
✓ Turntable Speed	0-20 round per minute
✓ Lifting Unite	Photoelectric switch for height control
✓ Film Stretching Unit	Frequency regulation (pre-stretch)
✓ Max. Package Weight	80 kg
✓ Pacakage Size (L x W x H)	(250~1200) x (200~400) x (250~1200) mm

JPI-SW3002

Technical Specifications:

	JPI-SW3004A	JPI-SW3004B	JPI-SW3004C	JPI-SW3004D
Power Supply	1 Phase, 220V / 240V 3 Phase, 380 V / 415 V / 440 V 50 / 60 Hz			
Power Consumption	1.3 kw	1.3 kw	1.3 kw	1.3 kw
Wrapping Height	2100 m/m	2100 m/m	2400 m/m	2400 m/m
Turntable Diameter	1500 mm	1800 mm	1500 mm	1800 mm
Turntable Height	80 mm	80 mm	80 mm	80 mm
Turntable Loading Weight	2000 Kg (4400 lbs)	2000 Kg (4400 lbs)	2000 Kg (4400 lbs)	2000 Kg (4400 lbs)
Turntable Speed	5 - 15 RPM (Adjustable Speed)			
Film Carriage Speed	5 M / min. (Adjustable Speed)			
Film Specification	PE stretch film core internal diameter: 76 mm, PE stretch film roll external diameter : 350 mm, width 550 mm			
Film Thickness	17-35 microns	17-35 microns	17-35 microns	17-35 microns
Dimensions (L x W x H)	2623 x 1500 x 2410 mm	2623 x 1800 x 2410 mm	2623 x 1500 x 2710 mm	2623 x 1800 x 2710 mm

Luggage Wrapping Machine



- ✓ Power Consumption 1 Phase, 220 V, 50 Hz, 1 kw
- ✓ Turntable Speed 0-20 round per minute
- ✓ Lifting Unite Photoelectric switch for height control
- ✓ Film Stretching Unit Frequency regulation (pre-stretch)
- ✓ Max. Package Weight 80 kg
- ✓ Pacakage Size (L x W x H) (250~1200) x (200~400) x (250~1200) mm
- ✓ Machine Dimension (L x W x H) 1600 x 600 x 1740 mm
- ✓ Machine Weight 150 kg

JPI-SW3003

Stretch Wrapping Machine - Heavy Duty

- ✓ Film carriage is equipped with hinged drive for smooth vertical movement. Adjustable Speed
- ✓ Turntable equipped with hinged drive, for stable turning during pallet loading. Adjustable Speed
- ✓ PLC control system for better functionality
- ✓ Inverter controlled motor speed for smooth and steady operation
- ✓ Two-dent turntable design for easy movability of machine
- ✓ Photoelectric cell to measure the pallet height
- ✓ Electromagnetic brake device to adjust the tension of stretch film
- ✓ Optional pre-stretch system to reduce film consumption
- ✓ Manual as well as auto operation mode
- ✓ Safety limit switch for stretch film rack



JPI-SW3004

Technical Specifications:

	JPI-SW3004A	JPI-SW3004B	JPI-SW3004C	JPI-SW3004D
Power Supply	1 Phase, 220V / 240V 3 Phase, 380 V / 415 V / 440 V 50 / 60 Hz			
Power Consumption	1.3 kw	1.3 kw	1.3 kw	1.3 kw
Wrapping Height	2100 m/m	2100 m/m	2400 m/m	2400 m/m
Turntable Diameter	1500 mm	1800 mm	1500 mm	1800 mm
Turntable Height	80 mm	80 mm	80 mm	80 mm
Turntable Loading Weight	2000 Kg (4400 lbs)	2000 Kg (4400 lbs)	2000 Kg (4400 lbs)	2000 Kg (4400 lbs)
Turntable Speed	5 - 15 RPM (Adjustable Speed)			
Film Carriage Speed	5 M / min. (Adjustable Speed)			
Film Specification	PE stretch film core internal diameter: 76 mm, PE stretch film roll external diameter : 350 mm, width 550 mm			
Film Thickness	17-35 microns	17-35 microns	17-35 microns	17-35 microns
Dimensions (L x W x H)	2623 x 1500 x 2410 mm	2623 x 1800 x 2410 mm	2623 x 1500 x 2710 mm	2623 x 1800 x 2710 mm

Stretch Wrapping Machine - Light Duty



- ✔ Automatic pressing, stretching, wrapping, cutting and clamping of pallet
- ✔ PLC controlled turntable and film carriage speed
- ✔ Pre-stretch function for film to reduce film consumption. (Optional feature)
- ✔ Can be installed in an automatic production line
- ✔ Can work with top sheet dispenser that is used to the top wrapping
- ✔ Photoelectric cell to measure the pallet height
- ✔ Standard Assembly includes:
 - Conveyor
 - Top Press System
 - Pre-stretch System
 - Auto Film Clamping and Cutting System

JPI-SW3005

Stretch Wrapping Machine - Heavy Duty

- ✔ Automatic pressing, stretching, wrapping, cutting and clamping of pallet
- ✔ PLC controlled turntable and film carriage speed
- ✔ Turntable with toothed wheel to support high weight loads
- ✔ Reel carriage unit complete with stretch film tension device
- ✔ Pre-stretch function for film to reduce film consumption. (Optional feature)
- ✔ Can be installed in an automatic production line
- ✔ Can work with top sheet dispenser that is used to the top wrapping
- ✔ Photoelectric cell to measure the pallet height
- ✔ Wrapping failure and broken film detection system
- ✔ Top press system to stabilize the loads (Optional)
- ✔ Standard Assembly includes: Conveyor, Pre-stretch System, Auto Film Clamping & Cutting System
- ✔ Optional: Safety fences, Pre-stretch system, Top sheet dispenser, Pacakage out system



JPI-SW3006

Technical Specifications:

	JPI-SW3005	JPI-SW3006
Power Supply	3 Phase, 220V / 380V / 415 V / 440 V 50 / 60 Hz	3 Phase, 220V / 380V / 415 V / 440 V 50 / 60 Hz
Power Consumption	2.8 kw	5.2 kw
Wrapping Height	2400 m/m	2400 m/m
Turntable Diameter	1800 mm	2000 mm
Conveyor Height	450~550 mm	650 mm
Turntable Loading Weight	2000 Kg (4400 lbs)	4000 Kg (8800 lbs)
Turntable Speed	5 - 15 RPM (Adjustable Speed)	5 - 15 RPM (Adjustable Speed)
Film Carriage Speed	5 M / min. (Adjustable Speed)	5 M / min. (Adjustable Speed)
Film Specification	PE stretch film core internal diameter: 76 mm, PE stretch film roll external diameter : 350 mm	
Film Thickness	17-35 microns	17-35 microns
Air Compressor	6 Kg/sq. cm	6 Kg/sq. cm
Dimensions (L x W x H)	2980 x 1800 x 2710 mm	2980 x 2175 x 3100 mm



JOY PACK INDIA PVT. LTD.
 46, Suvidha Kunj, Pitam Pura
 New Delhi - 110034 INDIA

Tel. : +91 9810023485 / 9312235318
 Fax : +91 11 47502936
 Email: info@joypackindia.com